Standard Form Number: SF-GOODS Revised on: May 24, 2004

Republic of the Philippines **University of the Philippines Mindanao** Mintal, Tugbok District, Davao City

Date: 30 June 2022

BID BULLETIN NO. 01

Rebidding for the Supply of Equipment (UPS, CCTV & Biometrics, Camera, Vault) for the ALAM-LSI Project (PBM 2022-11)

This Bid Bulletin is issued for the revisions in the <u>TECHNICAL SPECIFICATIONS</u>. **Please use the attached Revised Technical Specifications and the Price Schedules**.

For guidance of all concerned.

PROF. CLETO L. NAÑOLA JR.

PROF. CLETO L. NANOLA JR. Chair, Bids and Awards Committee for Goods

Received by the bidder:

Signature over printed name/date received

Item	Specification	Statement of Compliance
	General terms for all lots	[Bidders must state here either "Comply" or "Not Comply"
	For Equipment:	against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply"
	1) The equipment must come from a credible	or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturen's up amended sales literature
	manufacturer with support through a distributor in the country; and	in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data, as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence
	2) The equipment must be brand new and unused.	presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]

Technical Specifications

Item	Specification	Statement of Compliance							
LOT 1	High End Uninterruptible Power Supply (UPS) ABC: Php 500,0	00.00							
	Delivery period: Thirty (30) to ninety (90) calendar days Delivery and Installation: CARIM Bldg., UP Mindanao Mintal, Tugbok District, Davao City								
	Technical Specifications:								
	Mount: Rack								
	Phase: Single Phase								
	Topology: Double conversion online								
	Bypass: Built-in static bypass, Internal bypass (automatic and manual)								
	Backup time: At least 10 minutes at full load								
	Optional external bypass								
	 Smart-UPS at least 10KVA 								
	• Preferably inclusive of delivery, installation, materials, labor costs, and								
	all charges								
	 With at least 1 year warranty 								
	PLEASE INCLUDE BROCHURE OF EQUIPMENT/ITEM, WITH ITS MAKE/MOD ICATIONS. IF POSSIBLE, INCLUDE PERFORMANCE METRICS/REVIEWS.	EL/UNIT NUMBER AND							

LOT 2: SECURITY SYS	STEM (CCTV, BIOMETRIC LOCKS, ETC.)	
ABC: Php 350,000.00	· · · · · · · · · · · · · · · · · · ·	
	Delivery period: Thirty (30) to ninety (90) calendar days	
	CARIM Bldg., UP Mindanao Mintal, Tugbok District, Davi	ao City
1.) SECURII	Y SYSTEM (CCTV, BIOMETRIC LOCKS, ETC.)	
Technical Specif	ications:	
· · · · · · · · · · · · · · · · · · ·	Network Video Recorder 16ch (NVR)	
 Audio/Vid 	eo Inputs/Outputs: 16 ch up to 8 MP Resolution	
 Recording UXGA, 72 	g Resolutions: 8 MP, 6 MP, 5 MP, 4 MP, 3 MP, 1080p, 20p, VGA	
 Synchron 	ous Playback: 16-Channel	
Capability	r: 1-Channel at 8 MP, 4-Channel at 1080p	
	h: Incoming: 160 Mb/s Outgoing: 80 Mb/s	
	: TCP/IP, DHCP, Hik-Connect	
	nterface:1 x RJ45 1000M Self-Adaptive Ethernet	
	face: 2 x USB 2.0	
	POE Gigabit Switch 16 port	
	s IP Vandal Dome Indoor Cameras	
 At least 9 	0° viewing angle	
	ome Resolution TVL: at least 2 MP	
Mount Ty	pe: Wall, In-ceiling mount	
 Support v 	ideo Compression: H.264, MPEG4, MJPEG	
	Properties: Interface: 1 RJ45 10M / 100M ethernet port -485 interface	
 Network RTSP, PF 	Protocols: TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, PPoE	
Image Fra	ame Rate: 30 fps / 25 fps	
• Six (6) Units	IP Bullet Outdoor Cameras	
 At least 9 	0° viewing angle	
 Sensor at 	least 2 MP 1/2.5" CMOS Focal Length: 2.8mm	
 Supported MJPEG N 	d Video Compression: H.264, H.264+, H.265, H.265+, Iulti-View	
Analytics:	Motion Detection Line Crossing Detection	
 Intrusion 	Detection Exception Detection	
IP Rating	: IP67	
	nectors, UTP Cable CAT 6, Cables, and Related uit Materials, Assemblies, and Equipment	
Intrusion	Detection Exception Detection	
	t least 1 year warranty	
2.) BIOMETRIC	SYSTEM ATTENDANCE AND MAGNETIC DOOR LOCK	
Inclusions		
BIOMETRIC	SYSTEM ATTENDANCE (TCP/IP)	
 Fingerprir 	nt Capacity 3,000	
 Card Cap 	• •	
 Logs Cap 		
	cation TCP/IP, USB-Host, Wi-Fi (Optional)	

Jard Functions	
 Automatic Status Switch, Self-Service Query, Work Code, T9 Input, 9 Digit User 	
Query, Work Code, T9 Input, 9 Digit User	
ID, DST, Scheduled bell,SMS,RS232 Printer	
AC module 1:Exit Button, Door Lock, Alarm,12V OUT,AUX IN	
With ID Card, IC Card POE, 3G/4G, Battery Module, ADMS	
AC module 2: Exit Button, Door Lock, Alarm,12V OUT, AUX IN, Door Sensor, RS485	
Wiegand IN/OUT.	
NETIC DOOR LOCK	
sions	
IC Card at least 30 IC cards	
3 Magnetic Door Locks	
- 1 IC card for lock 1	
- 3 IC cards for lock 2	
- 30 IC cards for lock 3	
Exit switch	
	DEL/UNIT NUMBER AND
	N
• •	50
	avao Citv
5	
······································	
51 5	
5 5	
sions:	
built camera flash	
attery and battery charger (w/ extra battery)	
attery and battery charger (w/ extra battery)	
attery and battery charger (w/ extra battery) built WiFi & Bluetooth (preferably with NFC Connectivity)	
	ID, DST, Scheduled bell,SMS,RS232 Printer AC module 1:Exit Button, Door Lock, Alarm,12V OUT,AUX IN With ID Card, IC Card POE, 3G/4G, Battery Module, ADMS AC module 2: Exit Button, Door Lock, Alarm,12V OUT, AUX IN, Door Sensor, RS485 Wiegand IN/OUT. NETIC DOOR LOCK sions IC Card at least 30 IC cards 3 Magnetic Door Locks - 1 IC card for lock 1 - 3 IC cards for lock 2 - 30 IC cards for lock 3 Exit switch

SPECIFICATIONS. IF POSSIBLE, INCLUDE PERFORMANCE METRICS/REVIEWS.	
LOT 4: Secure Vault System ABC: Php 100,000.00	
Delivery period: Thirty (30) to sixty (60) calendar days	
Delivery and Installation: CARIM Bldg., UP Mindanao Mintal, Tugbok District, Da	vao City
Technical Specifications:	
• Exterior: Galvanized steel walls and door; Concealed hinges and	
recessed door type; Stainless steel handle with emergency release;	
Watertight Fire resistant Pre-Drilled Mounting Holes & Hardware	
 Preferably with humidity and temperature sensor 	
• Finish: Durable and scratch-resistant powder-coated interior and	
exterior finish; With air vents and insulation panels	
Size: Can fit at least A3-size documents	
• Interior dimension: at least 40 cm depth, 80 cm height, and 30 cm width	
• Secure locking mechanism: Key lock mechanism, Programmable	
digital lock Override access keys Motorized locking door bolts; Fail-safe	
lock/unlock during power outage	
With at least 1 year warranty	
NOTE: PLEASE INCLUDE BROCHURE OF EQUIPMENT/ITEM, WITH ITS MAKE/MODE	EL/UNIT NUMBER AND
SPECIFICATIONS. IF POSSIBLE, INCLUDE PERFORMANCE METRICS/REVIEWS.	

Price Schedule for Goods Offered from Within the Philippines [shall be submitted with the Bid if bidder is offering goods from within the Philippines]

For Goods Offered from Within the Philippines

Name of Bidder	Project ID No	Page	of

1	2	3	4	5	6	7	8	9	10
ltem	Description		Quan tity	Unit price EXW per item	Transportati on and all other costs incidental to delivery, per item	Sales and other taxes payable if Contract is awarded, per item	Cost of Incidental Services, if applicable, per item	Total Price, per unit (col 5+6+7+8)	Total Price delivered Final Destination (col 9) x (col 4)
	LOT 1: High-end UPS								
	 Technical Specifications: Mount: Rack Phase: Single Phase Topology: Double conversion online Bypass: Built-in static bypass, Internal bypass (automatic and manual) Backup time: At least 10 minutes at full load Optional external bypass Smart-UPS at least 10KVA Preferably inclusive of delivery, installation, materials, labor costs, and all charges With at least 1 year warranty NOTE: PLEASE INCLUDE BROCHURE OF EQUIPMENT/ITEM, WITH ITS MAKE/MODEL/UNIT 		1						

	NUMBER AND SPECIFICATIONS. IF POSSIBLE, INCLUDE PERFORMANCE METRICS/REVIEWS.				
	LOT 2: Security System (CCTV, biometric locks, etc.)				
1	CCTV KIT (Internet Protocol (IP) Cameras) Inclusions:	1			
	 *One (1) Unit Network Video Recorder 16ch (NVR) Audio/Video Inputs/Outputs: 16 ch up to 8 MP Resolution Recording Resolutions: 8 MP, 6 MP, 5 MP, 4 MP, 3 MP, 1080p, UXGA, 720p, VGA Synchronous Playback: 16-Channel Capability: 1-Channel at 8 MP, 4-Channel at 1080p Bandwidth: Incoming: 160 Mb/s Outgoing: 80 Mb/s Protocols: TCP/IP, DHCP, Hik-Connect Network Interface:1 x RJ45 1000M Self-Adaptive Ethernet USB Interface: 2 x USB 2.0 *One (1) Unit POE Gigabit Switch 16 port *Ten (10) Units IP Vandal Dome Indoor Cameras At least 90° viewing angle Monochrome Resolution TVL: at least 2 MP Mount Type: Wall, In-ceiling mount Support video Compression: H.264, MPEG4, MJPEG Network Properties: Interface Network Protocols: TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE Image Frame Rate: 30 fps / 25 fps *Six (6) Units IP Bullet Outdoor Cameras At least 90° viewing angle Sensor at least 2 MP 1/2.5" CMOS Focal Length: 2.8mm Supported Video Compression: H.264, H.264+, H.265, H.265+, MJPEG Multi-View Analytics: Motion Detection Line Crossing Detection Intrusion Detection Exception Detection IP Rating: IP67 *RJ 45 Connectors, UTP Cable CAT 6, Cables, and Related Wiring/Conduit Materials, Assemblies, and Equipment * With at least 1 year warranty 				

BIOMETRIC SYSTEM ATTENDANCE AND MAGNETIC DOOR LOCK Inclusions: BIOMETRIC SYSTEM ATTENDANCE (TCP/IP) • Fingerprint Capacity 3,000 • Card Capacity 10,000 (Optional) • Logs Capacity 100,000 • Communication TCP/IP, USB-Host, Wi-Fi (Optional) Standard Functions • Automatic Status Switch, Self-Service Query, Work Code, T9 Input, 9 Digit User • ID, DST, Scheduled bell,SMS,RS232 Printer • AC module 1:Exit Button, Door Lock, Alarm, 12V OUT, AUX IN, • With ID Card, IC Card POE, 3G/4G, Battery Module, ADMS • AC module 2: Exit Button, Door Lock, Alarm, 12V OUT, AUX IN, Door Sensor, RS485 • Wiegand IN/OUT. MAGNETIC DOOR LOCK Inclusions: • IC Card at least 30 IC cards • 3 Magnetic Door Locks • 1 IC card for lock 1 • 3 IC cards for lock 2 • 30 IC cards for lock 3 • Exit switch • Power supply • With at least 1 year warranty • NOTE: PLEASE INCLUDE BROCHURE OF EQUIPMENT/ITEM, WITH ITS MAKE/MODEL/UNIT NUMBER AND SPECIFICATIONS. IF POSSIBLE, INCLUDE PERFORMANCE METRICS/REVIEWS.				
LOT 3: Digital Camera with Accessories				
Digital Camera with Accessories Technical Specifications: • Type: Digital Single-lens Reflex (DSLR) • Sensor: Full frame • Lens Kit: 18-55mm f/4-5.6 with Lens Stabilization • Wide-angle Lens: 10-18mm f/4.5-5.6 or better	1			

 Macro Lens: 100mm f/2.8 with Lens Stabilization Photo: at least 24.1 megapixel or higher Video: 1080p resolution or higher Continuous Shooting: at least 5 fps ISO range: 100 - 25600 or higher Display: inbuilt liquid crystal display (LCD) touchscreen Storage: SD, SDHC, SDXC (UHS Speed Class 1 compatible) Inclusions: Inbuilt camera flash Battery and battery charger (w/ extra battery) Inbuilt WiFi & Bluetooth (preferably with NFC Connectivity) Storage: at least 2 x 64Gb or 1 x 128 Gb micro SDXC Camera Strap, camera bag, tripod, remote control With at least 1 year warranty NOTE: PLEASE INCLUDE BROCHURE OF EQUIPMENT/ITEM, WITH ITS MAKE/MODEL/UNIT NUMBER AND SPECIFICATIONS. IF POSSIBLE, INCLUDE PERFORMANCE METRICS/REVIEWS. 				
LOT 4: Secure Vault System				
 SECURE VAULT SYSTEM Technical Specifications: Exterior: Galvanized steel walls and door; Concealed hinges and recessed door type; Stainless steel handle with emergency release; Watertight Fire resistant Pre-Drilled Mounting Holes & Hardware Preferably with humidity and temperature sensor Finish: Durable and scratch-resistant powder-coated interior and exterior finish; With air vents and insulation panels Size: Can fit at least A3-size documents Interior dimension: at least 40 cm depth, 80 cm height, and 30 cm width Secure locking mechanism: Key lock mechanism, Programmable digital lock Override access keys Motorized locking door bolts; Fail-safe lock/unlock during power outage 	1			

•	With at least 1	year warranty	
•		INCLUDE BROCHURE OF	
		MAKE/MODEL/UNIT	
		NS. IF POSSIBLE, INCLU	DE PERFORMANC
	METRICS/REV	<mark>'IEWS.</mark>	

Name:			
inallic.			

Legal Capacity: _____

Signature: _____

Duly authorized to sign the Bid for and behalf of: _____