Standard Form Number: SF-GOODS Revised on: May 24, 2004

Republic of the Philippines **University of the Philippines Mindanao**

Mintal, Tugbok District, Davao City

November 14, 2022

BID BULLETIN NO. 01 Supply and Installation of Stadium Seats for the DC-UP Sports Complex (PBM 2022-28)

This Bid Bulletin is issued to inform the bidders of the following changes in the TECHNICAL SPECIFICATIONS:

From:	To:	
(1) Cheese head inner hex screw M10*20mm (with flexible flat washer)	(1) Cheese head inner hex screw M10*20mm – 40mm (with flexible flat washer)	
Other Information:		
WARRANTY: at least 1 year warranty		
SITE INSPECTION: Mondays to Thursdays, 8:30am – 11:00am		
CONTACT PERSON: Ar. Aika Santos, 09493363540, acsantos2@up.edu.ph		
CERTIFICATION: All documents must be in English. If it is in foreign language, it		
must be accompanied by a translation of the documents		
Please see attached Revised Technical Specifications to be submitted with the bid documents.		

The foregoing revised specifications should be incorporated in the Price Schedule to be submitted by the bidder.

For guidance of all concerned.

PROF. CLETO L. NAÑOLA JR.

Chair, Bids and Awards Committee for Goods

Received by the bidder:

Signature over printed name/Date received

Technical Specifications

Item	Specification	Statement of Compliance
		[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]

ITEM NO.	Specification	Statement of Compliance
	Supply and Installation of Stadium Seats for DC-UP Sports Complex	
	ABC = Php 11,700,000	
1	Supply and Installation of Stadium Seats for DC-UP Sports Complex- 1,488 pcs. Color Green Specifications: Backrest – HDPE as raw material, Drainage – Scupper design, Stanchion – Use high quality steel tube molding or aluminum Seat depth – 445mm, Seat w – 410mm, Seat H – 665mm, Seat c/c – 440-500mm, Seat base H – 430mm	
	450-480 450-480	
	Simple mount Specifications: Backrest Use HDPE as raw material, adopt blow molding craft. Drainage Scupper design, no (seeper) because of rainwater. Stanchion Use high quality steel tube molding or aluminum precision die-casting, surface phosphated, electrostatic gush model form. Installation Floor mount/ Riser mount/ Simple mount.	

Parts and tools needed for Installation:

- (2) Simple Mounted Stand 1 direct to plastic seat, 1 direct to concrete
- (4) 116*15 half-round head cross screws (with flexible flat washer)
- (at least 1) Philips screwdriver
- (2) M10*40 flat expansion nut
- (1) M10*20 hex screw (with flexible flat washer)
- (at least 1) No. 17 open-ended wrench
- (at least 1) Electric Hammer
- (at least 1) Hammer
- (at least 1) steel tape
- (1) Cheese head inner hex screw M10*20mm 40mm (with flexible flat washer)
- (at least 1) 8mm inner hex spanner
- Other tools/materials not mentioned that are deemed necessary for the installation

Seat dimensions:

- 1. Seat depth: 445mm
- 2. Seat width: 410mm
- 3. Seat height: floor mount 665mm and adjustable riser mount height
- 4. Seat c/c: 440 500mm or larger
- 5. Seat base height: floor mount 430mm and adjustable riser mount height
- 6. Backrest height: 330mm

Standard colors: 7colors



Option colors: 11colors



Production Standards:

Fire Resistance ---- Pass DIN 4102-1:1998 fire proof standard by SGS

Anti-UV ---- Pass ISO 4892-2:2006 and ISO 105-A02:1993 Cor2:2005

Anti-UV standard by SGS

Color fastness ---- ISO 105 B02 : 1999 : Xenon – Arc Lamp

000 WHITE

Loading ---- EN 12727 : 2000

WARRANTY: at least 1 year warranty

SITE INSPECTION: Mondays to Thursdays, 8:30am – 11:00am

CONTACT PERSON: Ar. Aika Santos, 09493363540, acsantos2@up.edu.ph CERTIFICATION: All documents must be in English. If it is in foreign language, it

must be accompanied by a translation of the documents in English.

LAYOUT/PHOTO OF INSTALLATION:





Note:

- Bidder must attach and submit brochure with the bid documents
- Bidder must present sample to UP Mindanao during post qualification.

ITEM NO.	Specification	Statement of Compliance
	Supply and Installation of Stadium Seats for DC-UP Sports Complex- 1,488 pcs. Color Red	•
2	Specifications: Backrest – HDPE as raw material,	
	Drainage – Scupper design,	
	Stanchion – Use high quality steel tube molding or aluminum	
	Seat depth – 445mm,	
	Seat w – 410mm,	
	Seat H – 665mm, Seat c/c – 440-500mm,	
	Seat base H – 430mm	
	450-480 450-480	
	- 445 - 	
	2000 2007	
	Simple mount	
	Specifications:	
	BackrestUse HDPE as raw material, adopt blow molding craft.	
	DrainageScupper design, no (seeper) because of rainwater.	
	StanchionUse high quality steel tube molding or aluminum precision die-casting.	
	surface phosphated, electrostatic gush model form. InstallationFloor mount/ Riser mount/ Simple mount.	
	NOTE: INSTALLATION BY SUPPLIER	
	Parts and tools needed for Installation:	
	• (2) Simple Mounted Stand – 1 direct to plastic seat, 1 direct to concrete	
	• (4) 116*15 half-round head cross screws (with flexible flat washer)	
	• (at least 1) Philips screwdriver	
	• (2) M10*40 flat expansion nut	
	• (1) M10*20 hex screw (with flexible flat washer)	

- (at least 1) No. 17 open-ended wrench
- (at least 1) Electric Hammer
- (at least 1) Hammer
- (at least 1) steel tape
- (1) Cheese head inner hex screw M10*20mm 40mm (with flexible flat washer)
- (at least 1) 8mm inner hex spanner
- Other tools/materials not mentioned that are deemed necessary for the installation

Seat dimensions:

- 1. Seat depth: 445mm
- 2. Seat width: 410mm
- 3. Seat height: floor mount 665mm and adjustable riser mount height
- 4. Seat c/c: 440 500mm or larger
- 5. Seat base height: floor mount 430mm and adjustable riser mount height
- 6. Backrest height: 330mm

Standard colors: 7colors



Option colors: 11colors



Production Standards:

Fire Resistance ---- Pass DIN 4102-1:1998 fire proof standard by SGS

Anti-UV ---- Pass ISO 4892-2:2006 and ISO 105-A02:1993 Cor2:2005

Anti-UV standard by SGS

Color fastness ---- ISO 105 B02: 1999: Xenon – Arc Lamp

Loading ---- EN 12727 : 2000

WARRANTY: at least 1 year warranty

SITE INSPECTION: Mondays to Thursdays, 8:30am – 11:00am

CONTACT PERSON: Ar. Aika Santos, 09493363540, acsantos2@up.edu.ph

CERTIFICATION: All documents must be in English. If it is in foreign language, it must

be accompanied by a translation of the documents in English.

LAYOUT/PHOTO OF INSTALLATION:





Note:

- Bidder must attach and submit brochure with the bid documents
- Bidder must present sample to UP Mindanao during post qualification.

ITEM		
NO.	Specification	Statement of Compliance
3	Supply and Installation of Stadium Seats for DC-UP Sports Complex- 1,488 pcs. Color Blue Specifications: Backrest – HDPE as raw material, Drainage – Scupper design, Stanchion – Use high quality steel tube molding or aluminum Seat depth – 445mm, Seat w – 410mm, Seat H – 665mm, Seat c/c – 440-500mm, Seat base H – 430mm	
	450-480 450-480	
	Simple mount Specifications: BackrestUse HDPE as raw material, adopt blow molding craft. DrainageScupper design, no (seeper) because of rainwater. Stanchion	
	InstallationFloor mount/Riser mount/Simple mount.	
	NOTE: INSTALLATION BY SUPPLIER Parts and tools needed for Installation: • (2) Simple Mounted Stand – 1 direct to plastic seat, 1 direct to concrete • (4) 116*15 half-round head cross screws (with flexible flat washer) • (at least 1) Philips screwdriver • (2) M10*40 flat expansion nut • (1) M10*20 hex screw (with flexible flat washer)	

- (at least 1) No. 17 open-ended wrench
- (at least 1) Electric Hammer
- (at least 1) Hammer
- (at least 1) steel tape
- (1) Cheese head inner hex screw M10*20mm 40mm (with flexible flat washer)
- (at least 1) 8mm inner hex spanner
- Other tools/materials not mentioned that are deemed necessary for the installation

Seat dimensions:

- 1. Seat depth: 445mm
- 2. Seat width: 410mm
- 3. Seat height: floor mount 665mm and adjustable riser mount height
- 4. Seat c/c: 440 500mm or larger
- 5. Seat base height: floor mount 430mm and adjustable riser mount height
- 6. Backrest height: 330mm

Standard colors: 7colors



Option colors: 11colors



Production Standards:

Fire Resistance ---- Pass DIN 4102-1:1998 fire proof standard by SGS

Anti-UV ---- Pass ISO 4892-2:2006 and ISO 105-A02:1993 Cor2:2005

Anti-UV standard by SGS

Color fastness ---- ISO 105 B02: 1999: Xenon – Arc Lamp

Loading ---- EN 12727 : 2000

WARRANTY: at least 1 year warranty

SITE INSPECTION: Mondays to Thursdays, 8:30am – 11:00am

CONTACT PERSON: Ar. Aika Santos, 09493363540, acsantos2@up.edu.ph

CERTIFICATION: All documents must be in English. If it is in foreign language, it must

be accompanied by a translation of the documents in English.







Note:

- Bidder must attach and submit brochure with the bid documents
- Bidder must present sample to UP Mindanao during post qualification.